

Model: SAVANNAH ANTRACITA L 59,6X59,6(A)

Codes: 100337273

Water absorption: Bla - Porcelanico (E<=0.1%)





DIMENSIONAL FEATURES UNE-EN ISO 10545-2			
Length and width deviation	Below 0.15%	+/-0.3%*	
Side straightness deviation	Below 0.15%	+/-0.3%*	
Squareness deviation	Below 0.15%	+/-0.3%*	
Surface flatness deviation	Below 0.15%	+/-0.4%*	
*ISO-13006:2018 UNE-EN 14411:2016			

MECHANICAL FEATURES UNE-EN ISO 10545-4-6-7-11		
Crazing resistance	Resists 3 cycles	

*ISO-13006:2018 UNE-EN 14411:2016

HYGIENIC FEATURES UNE-EN ISO 10545-13-14:1995		
Chemical resistance	Class "A" for swimming pools and cleaning products (resists attack). Minimum Class "B" for acids and bases	B Min.*
Stain resistance *ISO-13006:2018 UNE-EN 14411:2016	Class 5. Easy cleaning with water	3 Min.*

ANTI-SLIP VALUE EN 16165: 2022 / ASTM C1028		
Dynamic coefficient of friction	>0,42	
*ISO-13006:2018 UNE-EN 14411:2016		

PACKING		
Sales units per box	1.776073 M2/BOX	
Sales units per pallet	56.834328 M2/PAL	
Sales units per unit	0.355215 M2/PIECE	

SCOPE OF USE		
Technical code-1	6 - Use on heavy traffic floors	

System Certification









RECOMMENDED USE LOCATIONS

Single-family dwelling

Indoor Premises - Dry: Room, room, bedroom or other enclosure without direct access to the outdoors.

Collective housing

Indoor Premises - Residential - Dry: Entrance, living room, dining room, professional office with reception of customers

Indoor Premises - Housing - Dry: Bedrooms, personal office, storage room, changing room

Various

Cladding of bonded or mixed facades

Facade cladding with mechanical anchors

Kitchen worktops, bars, restaurants

Public bathroom countertops

System Certification





