

Model: SPIGA CORAL TOPO 45X120(A)

Codes: 100330321

Water absorption: BIII - Revestimiento (10%<=E<=20%)





| DIMENSIONAL FEATURES UNE-EN ISO 10545-2 | | | |
|--|-------------|----------|--|
| Thickness | 11 MM | +/-5%* | |
| Width | 450 MM | | |
| Length | 1200 MM | | |
| Length and width deviation | Below 0.15% | +/-0.3%* | |
| Side straightness deviation | Below 0.15% | +/-0.3%* | |
| Squareness deviation | Below 0.15% | +/-0.3%* | |
| Surface flatness deviation | Below 0.15% | +/-0.4%* | |

^{*}ISO-13006:2018 UNE-EN 14411:2016

| MECHANICAL FEATURES UNE-EN ISO 10545-4-6-7-11 | | | |
|--|------------------|------------|--|
| Breaking strength | >1100 N | >600N* | |
| Modulus of rupture | >23 N/MM2 | >=12N/mm2* | |
| Crazing resistance | Resists 3 cycles | | |

| "ISO-13006:2018 | ONF-FIN | 14411:2016 |
|-----------------|---------|------------|
| | | |

| HYGIENIC FEATURES UNE-EN ISO 10545-13-14:1995 | | |
|---|--|---------|
| Chemical resistance | Class "A" for swimming pools and cleaning products (resists attack). Minimum Class "B" for acids and bases | B Min.* |
| Stain resistance | Class 5. Easy cleaning with water | 3 Min.* |
| *ISO-13006:2018 UNE-EN 14411:2016 | | |

| SCOPE OF USE | | |
|---------------------|-----------------|--|
| Technical code-1 | Use on walls | |
| PACKING | | |
| Sales units per box | 1.619958 M2/BOX | |

System Certification







Sales units per pallet

Sales units per unit

64.798315 M2/PAL

0.539986 M2/PIECE