

Model: ADDA BONE L 59,6X59,6(A)

Codes: 100324843

Water absorption: Bla - Porcelanico (E<=0.1%)





DIMENSIONAL FEATURES UNE-EN ISO 10545-2				
Thickness	8.5 MM	+/-5%*		
Width	596 MM			
Length	596 MM			
Length and width deviation	Below 0.15%	+/-0.3%*		
Side straightness deviation	Below 0.15%	+/-0.3%*		
Squareness deviation	Below 0.15%	+/-0.3%*		
Surface flatness deviation	Below 0.15%	+/-0.4%*		

^{*}ISO-13006:2018 UNE-EN 14411:2016

MECHANICAL FEATURES
UNE-EN ISO 10545-4-6-7-11

2338.2 N >1300N* Breaking strength Modulus of rupture 54.8 N/MM2 >=35N/mm2* Crazing resistance Resists 3 cycles

*ISO-13006:2018 UNE-EN 14411:2016

HYGIENIC FEATURES UNE-EN ISO 10545-13-14:1995

Chemical resistance Class "A" for swimming pools and cleaning products B Min.* (resists attack). Minimum Class "B" for acids and bases Class 5. Easy cleaning with water 3 Min.* Stain resistance

*ISO-13006:2018 UNE-EN 14411:2016

SCOPE OF USE

Technical code-1 Use on heavy traffic floors

AN	H-SLIP	VAL	UE
EN 1616	5: 2022 /	ASTM	C1028

Slip resistance (pendulum-wet) CL1

*ISO-13006:2018 UNE-EN 14411:2016

	PACKING	
Sales units per box	1.776073 M2/BOX	
Sales units per pallet	56.834328 M2/PAL	
Sales units per unit	0.355215 M2/PIECE	

System Certification





