

Model: ALPI VERDE POLISHED 120X120 (6)(A) Codes: 100272172 Absorption: Bla - Porcelanico (E<=0.1%)





DIMENSIONAL FEATURES UNE-EN ISO 10545-2			
Length	1200 MM		
Thickness	6 MM		
Width	1200 MM		
Length and width deviation	Below 0.15%	+/-0.3%*	
Side straightness deviation	Below 0.15%	+/-0.3%*	
Squareness deviation	Below 0.15%	+/-0.3%*	
Surface flatness deviation	Below 0.15%	+/-0.4%*	
*ISO-13006:2015 UNE-EN 14411:2017			

MECHANICAL FEATURES UNE-EN ISO 10545-4-6-7-11		
Breaking strenght	>1100 N	
Modulus of rupture	>45 N/MM2	
Abrasion resistance	<140	
*ISO-13006:2015 UNE-EN 14411:2017		

HYGIENIC FEATURES UNE-EN ISO 10545-13-14			
Chemical resistance	MIN B		
Stain resistance	5		
Flammability	A1		
*ISO-13006:2015 UNE-EN 14411:2017			

	ANTI-SLIP VALUE CEN/TS 41901/02, DIN-51130 y ASTM A137.1
Slip resistance (pendulum-wet)	CLO
4s	DRY>36-LOW_WET<25-HIGH
Slip resistance (pendulum-dry)	>45
*ISO-13006:2015 UNE-EN 14411:2017	
	SCOPE OF USE

Technical code-1 Technical code-2

Use on light traffic floors Dry interior floors

> System Certification SGS SGS SGS

Do not use cleaning agents containing hydrofluoric acid. It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint. For big sizes, it is recomended to fix with mortars containing polymeric additives and to use the double glueing technique. Mosaic tiles must be grouted. This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by PORCELANOSA S.A.

100272172 ALPI VERDE POLISHED



PACKING		
Sales units per box	2.88 M2/BOX	
Sales units per pallet	74.88 M2/PAL	
Sales units per unit	1.44 M2/PIECE	

