

Model: ARTIC L 80X80(A) Codes: 100323092

Water absorption: Bla - Porcelanico (E<=0.1%)





DIMENSIONAL FEATURES  UNE-EN ISO 10545-2			
Thickness	8.5 MM	+/-5%*	
Width	800 MM		
Length	800 MM		
Length and width deviation	Below 0.15%	+/-0.3%*	
Side straightness deviation	Below 0.15%	+/-0.3%*	
Squareness deviation	Below 0.15%	+/-0.3%*	
Surface flatness deviation	Below 0.15%	+/-0.4%*	

<sup>\*</sup>ISO-13006:2018 UNE-EN 14411:2016

MECHANICAL FEATURES  UNE-EN ISO 10545-4-6-7-11			
Breaking strength	2140 N	>1300N*	
Modulus of rupture	54.1 N/MM2	>=35N/mm2*	
Abrasion resistance	PEI 5 / 12000v		
Crazing resistance	Resists 3 cycles		

<sup>\*</sup>ISO-13006:2018 UNE-EN 14411:2016

	HYGIENIC FEATURES UNE-EN ISO 10545-13-14:1995	
Chemical resistance	Class "A" for swimming pools and cleaning products (resists attack). Minimum Class "B" for acids and bases	B Min.*
Stain resistance	Class 5. Easy cleaning with water	3 Min.*

*ISO-13006:2018	UNE-EN	14411:2016

	SCOPE OF USE	
Technical code-1	Use on heavy traffic floors	

		ANTI-SLIP VALUE EN 16165: 2022 / ASTM C1028
Slip resistance (pendulum-wet)	CL0	
*ISO-13006:2018 UNE-EN 14411:2016		

	PACKING	
Sales units per box	1.28 M2/BOX	
Sales units per pallet	57.6 M2/PAL	
Sales units per unit	0.64 M2/PIECE	

System Certification





