







DIMENSIONAL FEATURES UNE-EN ISO 10545-2		
Length	2500 MM	
Width	1200 MM	
Length and width deviation	Below 0.15%	+/-0.3%*
Side straightness deviation	Below 0.15%	+/-0.3%*
Squareness deviation	Below 0.15%	+/-0.3%*
Surface flatness deviation	Below 0.15%	+/-0.4%*
*ISO-13006:2015 UNE-EN 14411:2017		
	ANTI-SLIP VALUE	
	CEN/TS 41901/02, DIN-51130 y ASTM A137.1	
4s	DRY>36-LOW_WET<25-HIGH	
*ISO-13006:2015 UNE-EN 14411:2017		
	SCOPE OF USE	
Technical code-2	Dry interior floors	
PACKING		
Sales units per box	3 M2/BOX	
Sales units per pallet	66 M2/PAL	



Sales units per unit

Do not use cleaning agents containing hydrofluoric acid. It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint. For big sizes, it is recomended to fix with mortars containing polymeric additives and to use the double glueing technique. Mosaic tiles must be grouted. This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by PORCELANOSA S.A.

3 M2/PIECE