

Model: CLASSIC 1L HERRINGBONE CAMEL


Codes: 100286565

Group: G-244

Format: 13X72,5X1,4CM



### COMPOSITION



	Size	Material	Type of material
Layer 1	0.060-0.070	Oil	
Layer 2	2.5	Hardwood Layer	Oak wood
Layer 3	9.5	Intermediate Layer	PINE
Layer 4	2.0	Backside	PINE

### TOLERANCES

Squareness of the item	0.2% of width.	
Curvature	0.1% of length.	

### LABORATORY TESTS

Thermal conductivity	0.14 W/M*K	UNE-EN 12667:2002*
Heat resistance	0.103 M2*K/W	UNE-EN 12667:2002*
Formaldehyde emissions	0.024 mg/m3	EN - 717/1:2006*
Moisture content	7% +/-2%	UNE-EN 13183-1 / AC:2004*
Flammability	Dfl-S1	UNE EN 13501-1:2007*
Bulk density	min 500kg/m3	UNE-EN 323:1994*
Slip resistance (pendulum-wet)	CL 2 (40)	UNE 41901*
Slip resistance (pendulum-dry)	CL 3 (65)	UNE 41902*
Slip resistance (dcof)	0.63	ANSI A137.1*



## FEATURES

- It is one of the easiest to install and safest systems in the market. We just need to adjust the board to be installed longitudinally to the one already placed, by applying a soft pressure without the need for any type of tool. Both pieces will fit and will be secured thanks to the safety tab. It is just as simple to take apart, which makes for a quick disassembly
- Applying a color oil or varnish on the wood surface in order to get different color ranges.
- L'ANTIC COLONIAL's varnishing, in two finishes, APRESTO (gloss) and APRESTO MATE (matte), provides a unique surface quality that satisfies the most demanding requirements. Advantages: It achieves the highest cleanliness because, since the pores are sealed, dirt and dust remain on the surface and can be easily cleaned.
- Is suitable for installing on water radiant heating
- Material with many knots on its surface that can have different sizes depending on the type of wood. These, along with any cracks that may appear, are covered with putty.
- Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.
- There are consistent color changes between pieces.
- Independent (non-governmental) certificate that guarantees consumers that forest products come from rationally exploited forests
- 2.5 mm
- Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.
- Slight smoothing of the wood using a brush to achieve a surface with a slight relief.
- Beveled cut on all 4 edges of the board for emphasizing size
- Quality product made with selected raw materials, guaranteeing its full residential use for 30 years as provided by L' Antic Colonial.
- Format where only one board has been used to finish the entire base surface
- It is necessary to apply adhesive for installing it.
- Made with oak wood.
- Material from a European country.
- Structure formed by an upper layer that shows the noble aspect of the material, an intermediate layer of wood of different typology, depending on the collection, or HDF board that compensates the tensions between the different parts and a lower plywood that provides dimensional stability.
- It is necessary to apply adhesive for installing it.

## PACKING

Sales units per box	0.65975 M2/BOX
Sales units per pallet	42.224 M2/PAL
Sales units per square meter	1 M2
Sale unit	M2
Base unit	ST
Net weight	8.965517 KG/M2
Gross weight	9.485411 KG/M2

## SPECIAL PIECES

SAP	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net Weight	Gross weight
100298244	IGUALACION CLASSIC HERRINGBONE CAMEL	G-161	10 PIECES/BOX	1000 PIECES/PAL	8.23 PIECES/M2	-	-	1 KG/PIECES	1.02 KG/PIECES
100298253	TRANSICION CLASSIC HERRINGBONE CAMEL	G-161	10 PIECES/BOX	1000 PIECES/PAL	9.26 PIECES/M2	-	-	1 KG/PIECES	1.02 KG/PIECES
100298280	ZOCALO CLASSIC HERRINGBONE CAMEL 8X220	G-128	12 PIECES/BOX	600 PIECES/PAL	5.68 PIECES/M2	-	-	1.33 KG/PIECES	1.38 KG/PIECES

