## L'ANTIC COLONIAL

Model: ESSENTIAL SPIKE CARRARA

Codes: 100308734 Group: G-146

Format: 24,5X33,4X1



	RECOMMENDATIONS	
Recommended adhesive	100031188 SUPER-ONE N BLANCO 25KG	
Recommended joint	100236442 COLORSTUK BLANCO N 0-4 5KG	
Recommended joint (wet area)	100236442 COLORSTUK BLANCO N 0-4 5KG	100086920 FILA FOB XTREME 1L
Recommended adhesive (wet area)	100031188 SUPER-ONE N BLANCO 25KG	

	TECHNICAL INFORMATION	
Slip resistance (pendulum-wet)	CL 1 (25)	
Water absorption at atmospheric pressure	0.1-0.2%	UNE-EN 13755:2002*
Slip resistance (pendulum-dry)	CL 3 (78)	
Flammability	Clase A1f I/Clase A1	UNE-EN 13501-1:2007+A1:2010*
Use	FLOOR TILES	
Slip resistance (dcof)	0.50	ANSI 137.1*
Composition	MARBLE	

## **FEATURES**



Product manufactured on a mesh that makes installation easier.



Material suitable for use on shower floors.





Material suitable for use on indoor floors.



Material suitable for use on indoor walls.

|--|--|--|

Gloss-free



Material only suitable for low-traffic floors (private setting.)



Material suitable for use on shower walls.

PACKING		
Sales units per square meter	12.220459 PIECES/M2	
Sales units per box	10 PIECES/BOX	
Sales units per unit	1 PIECES	
Sale unit	ST	
Base unit	ST	
Net weight	2.195 KG/PIECES	
Gross weight	2.272 KG/PIECES	





It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A.U., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive agents, such as acids or solvents, or metallic or sharp elements for cleaning. In public places mosaics must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.U.

09/04/2023