

Model: GLEM WHITE POLISHED 120X120 (6)(A)

Codes: 100262248

Absorption: Bla - Porcelanico (E<=0.1%)





	DIMENSIONAL FEATURES UNE-EN ISO 10545-2	
Length	1200 MM	
Thickness	6 MM	
Width	1200 MM	
Length and width deviation	Below 0.15%	+/-0.3%*
Side straightness deviation	Below 0.15%	+/-0.3%*
Squareness deviation	Below 0.15%	+/-0.3%*
Surface flatness deviation	Below 0.15%	+/-0.4%*

^{*}ISO-13006:2015 UNE-EN 14411:2017

	MECHANICAL FEATURES UNE-EN ISO 10545-4-6-7-11
Breaking strenght	>1100 N
Modulus of rupture	>45 N/MM2
Abrasion resistance	<140

^{*}ISO-13006:2015 UNE-EN 14411:2017

		ENIC FEATURES EN ISO 10545-13-14	
Chemical resistance	MIN B		
Stain resistance	5		
Flammability	A1		
*ISO-13006:2015 UNE-EN 14411:2017			

	ANTI-SLIP VALUE CEN/TS 41901/02, DIN-51130 y ASTM A137.1
Slip resistance (pendulum-wet)	CLO
4s	DRY>36-LOW_WET<25-HIGH
Slip resistance (pendulum-dry)	>45
*ISO-13006:2015 UNE-EN 14411:2017	

	SCOPE OF USE
Technical code-1	Use on light traffic floors
Technical code-2	Dry interior floors

System Certification









100262248 GLEM WHITE POLISHED



	PACKING	
Sales units per box	2.88 M2/BOX	
Sales units per pallet	74.88 M2/PAL	
Sales units per unit	1.44 M2/PIECE	

System Certification





