L'ANTIC COLONIAL

Model: HERITAGE GIRONA

Codes: 100336786 Group: G-226

Format: 20X20X0,85CM



	RECOMMENDATIONS
Recommended adhesive	100201543 ONE-FLEX PREMIUM GRIS 25KG
Recommended joint	100236449 COLORSTUK RAPID CEMENTO N 5KG
Recommended joint (wet area)	100236449 COLORSTUK RAPID CEMENTO N 5KG
Recommended adhesive (wet area)	100201543 ONE-FLEX PREMIUM GRIS 25KG

FEATURES









Material suitable for use on indoor walls.



Material recommended for installation on the floor.

	∄)
_ \	\smile

Material suitable for use on shower walls.



Material suitable for use on indoor floors.



There are slight color changes between pieces.

DIMENSIONAL FEATURES				
Length and width deviation	±0.5%	UNE-EN ISO 10545-2*		
Side straightness deviation	±0.5 %	UNE-EN ISO 10545-2*		
Orthogonality deviation	±0.5%	UNE-EN ISO 10545-2*		
Surface flatness deviation	+0.5 %	UNF-EN ISO 10545-2*		

PHYSICAL PROPERTIES				
Water absorption	Bla	ISO 10545-3*		
Breaking strength	>2100 N	>1300N*		
Resistance to thermal shock	PASS	ISO 10545-9*		
Crack resistance	PASS	ISO 10545-11*		
Flammability	A1f I/A1	EN 13501-1*		
Flexural strength	>51 MPA	ISO 10545-4*		
Slip resistance (pendulum-wet)	CL 1 (28)			
Slip resistance (ramp)	R9	DIN 51130*		
Slip resistance (pendulum-dry)	CL 3 (80)			
Dynamic coefficient of friction	0.72			
Abrasion resistance	PEI 3			





It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A.U., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use cleaning agents containing hydrofluoric acid. In public places the tiles must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.U.

20/01/2024

HERITAGE GIRONA

Net weight

Gross weight

L'ANTIC COLONIAL

CHEMICAL PROPERTIES				
Stain resistance	CL 5	ISO 10545-14*		
Resistance to chemicals	GA/GLA/GHA	ISO 10545-13*		
PACKING				
Sales units per box	0.88 M2/BOX			
Sales units per pallet	52.8 M2/PAL			
Sales units per unit	0.04 M2/PIECE			
Sale unit	M2			
Base unit	ST			

18.75 KG/M2

19.4 KG/M2



