Model: JAVA 1L NATURAL Codes: 100270881 Group: G-257 Format: 9X54X1,4CM

Squareness of the item



COMPOSITION								
		Size	Material	Type of material				
	Layer 1	0.060-0.070	Varnish	APRESTO MATTE				
	Layer 2	3	Hardwood Layer	Oak wood				
	Layer 3	9	Intermediate Layer	Coniferous wood slats				
	Layer 4	2	Backside	Coniferous Wood				
TOLERANCES								

0.2% of width.

LABORATORY TESTS							
Thermal conductivity	0.108 W/M*ºK W/M*K	UNE-EN 12667:2002**					
Formaldehyde emissions	Clase E1	EN-717/1:2006**					
Flammability	Dfl-S1	UNE EN 13501-1:2007**					
Biological durability	Clase 2						
Slip resistance (pendulum-wet)	CL 2 (40)	UNE 41901*					
Slip resistance (pendulum-dry)	CL 3 (65)	UNE 41902*					
Slip resistance (dcof)	0.63	ANSI A137.1*					



It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A.U., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive cleaning agents, such as acids, or metallic or sharp elements. In public places this material must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.U.

L'ANTIC COLONIAL

100270881 JAVA 1L NATURAL

FEATURES							
This installation system consists in assembling the boards. their edges by applying a slight pressure on the boards. bonded with white glue. Tools are needed for the instal	. The boards are then 🛛 🚺	Applying a color oil or varnish on the wood surface in order to get different color ranges.					
Slight smoothing of the wood using a brush to achieve a relief.	a surface with a slight	Beveled cut on all 4 edges of the board for emphasizing size					
L'ANTIC COLONIAL's varnishing, in two finishes, APREST MATE (matte), provides a unique surface quality that sa demanding requirements. Advantages: It achieves the h because, since the pores are sealed, dirt and dust rema be easily cleaned.	atisfies the most highest cleanliness	Quality product made with selected raw materials, guaranteeing its full residential use for 30 years as provided by L' Antic Colonial.					
Is suitable for installing on water radiant heating	T and the second se	Format where only one board has been used to finish the entire base surface					
Material with some knots on its surface that can have d on the type of wood. These, along with any cracks that with putty.		It is necessary to apply adhesive for installing it.					
OAK Made with oak wood.		There are considerable color changes between pieces.					
Material from an Asian country.		Structure formed by an upper layer that shows the noble aspect of the material, an intermediate layer of wood of different typology, depending on the collection, or HDF board that compensates the tensions between the different parts and a lower plywood that provides dimensional stability.					
3 mm	S.	It is necessary to apply	adhesive for installing it.				
	PACKIN	IG					
Sales units per box 0.5	582996 M2/BOX						
Sales units per pallet 51	1.303644 M2/PAL						
Sales units per square meter 11	M2						
Sale unit Mi	12						
Base unit ST	ſ						
Net weight 10	0.085833 KG/M2						
Gross weight 10	0.518083 KG/M2						



It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A.U., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive cleaning agents, such as acids, or metallic or sharp elements. In public places this material must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.U.