## L'ANTIC COLONIAL

Model: MONARCH 1L VICTORIA

Codes: 100287243 Group: G-263

Format: 25X220X1,9CM



#### **COMPOSITION** Size Material Type of material 0.060-0.070 Varnish Apresto Mate treatment Layer 2 Hardwood Layer Oak wood Intermediate Laver Layer 3 Oak wood Layer 4 Backside Oak wood

LABORATORY TESTS									
Thermal conductivity	0.170 W/mk	UNE-EN 12667:2002*							
Formaldehyde emissions	Class E0	EN 717*							
Moisture content	5-9%	EN 13489*							
Flammability	Cfl-s1	EN 13501*							
Critical radiant flux	4.68 kW/m2	ASTM E 648*							
Slip resistance (pendulum-wet)	CL 3 (60)	UNE 41901*							
Slip resistance (pendulum-dry)	CL 3 (60)	UNE 41902*							
Slip resistance (dcof)	0.71	ANSI A137.1*							

## **FEATURES**



This installation system consists in assembling the boards with slots and cuts or their edges by applying a slight pressure on the boards. The boards are then bonded with white glue. Tools are needed for the installation.



Slight smoothing of the wood using a brush to achieve a surface with a slight relief.



Applying a color oil or varnish on the wood surface in order to get different color ranges.



Beveled cut on all 4 edges of the board for emphasizing size



L'ANTIC COLONIAL's varnishing, in two finishes, APRESTO (gloss) and APRESTO MATE (matte), provides a unique surface quality that satisfies the most demanding requirements. Advantages: It achieves the highest cleanliness because, since the pores are sealed, dirt and dust remain on the surface and can be easily cleaned.



Quality product made with selected raw materials, guaranteeing its full residential use for 30 years as provided by  $L^\prime$  Antic Colonial.



Is suitable for installing on water radiant heating



Material with many knots on its surface that can have different sizes depending on the type of wood. These, along with any cracks that may appear, are covered with putty.



It is necessary to apply adhesive for installing it.

Material from a European country.



Material from an Asian country.

Made with oak wood.



There are considerable color changes between pieces.



Structure formed by an upper layer that shows the noble aspect of the material, an intermediate layer of wood of different typology, depending on the collection, or HDF board that compensates the tensions between the different parts and a lower plywood that provides dimensional stability.



5 mm



It is necessary to apply adhesive for installing it.





It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A.U., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive cleaning agents, such as acids, or metallic or sharp elements. In public places this material must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.U.

### MONARCH 11 VICTORIA

# L'ANTIC COLONIAL

	PACKING
Sales units per box	2.2 M2/BOX
Sales units per pallet	114.4 M2/PAL
Sales units per square meter	1 M2
Sale unit	M2
Base unit	ST
Net weight	13.181818 KG/M2
Gross weight	13.303636 KG/M2

SPECIAL PIECES											
SAP	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net Weight	Gross weight		
100297468	IGUALACION MONARCH VICTORIA 4,5X270X1,3	G-161	10 PIECES/BOX	1000 PIECES/PAL	8.23 PIECES/M2	-	=	1 KG/PIECES	1.02 KG/PIECES		
100297523	MAMPERLAN MONARCH VICTORIA 7X120X3	G-163	2 PIECES/BOX	200 PIECES/PAL	11.9 PIECES/M2	-	-	1.58 KG/PIECES	1.64 KG/PIECES		
100297508	TRANSICION MONARCH VICTORIA 4X270X1,3	G-161	10 PIECES/BOX	1000 PIECES/PAL	9.26 PIECES/M2	-	-	1 KG/PIECES	1.02 KG/PIECES		
100297550	ZOCALO MONARCH VICTORIA 8X220X1,4	G-128	12 PIECES/BOX	600 PIECES/PAL	5.68 PIECES/M2	-	-	1.33 KG/PIECES	1.38 KG/PIECES		





It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A.U., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive cleaning agents, such as acids, or metallic or sharp elements. In public places this material must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.U.

17/08/2023