

Model: NEWPORT BEIGE ANT.L 59,6X59,6(A)

Codes: 100325643

Water absorption: Bla - Porcelanico (E<=0.1%)





DIMENSIONAL FEATURES UNE-EN ISO 10545-2		
Thickness	8.5 MM	+/-5%*
Width	596 MM	
Length	596 MM	
Length and width deviation	Below 0.15%	+/-0.3%*
Side straightness deviation	Below 0.15%	+/-0.3%*
Squareness deviation	Below 0.15%	+/-0.3%*
Surface flatness deviation	Below 0.15%	+/-0.4%*

^{*}ISO-13006:2018 UNE-EN 14411:2016

MECHANICAL FEATURES
UNE-EN ISO 10545-4-6-7-11

PEI 4 / 1500v Abrasion resistance Crazing resistance Resists 3 cycles

HYGIE	ENIC	FEAT	JRES
UNE-EN	SO 10	545-13-1	14:1995

Chemical resistance Class "A" for swimming pools and cleaning products B Min.* (resists attack). Minimum Class "B" for acids and bases

Stain resistance Class 5. Easy cleaning with water 3 Min.*

*ISO-13006:2018 UNE-EN 14411:2016

ANTI-SLIP VALUE EN 16165: 2022 / ASTM C1028

Dynamic coefficient of friction >0.42 CL3 Slip resistance (pendulum-wet)

*ISO-13006:2018 UNE-EN 14411:2016

	PACKING
Sales units per box	1.776073 M2/BOX
Sales units per pallet	56.834328 M2/PAL
Sales units per unit	0.355215 M2/PIECE

	SCOPE OF USE
ochnical code 1	6. Use an heavy traffic floors

System Certification







^{*}ISO-13006:2018 UNE-EN 14411:2016



RECOMMENDED USE LOCATIONS

Single-family dwelling

Indoor Premises - Dry: Room, room, bedroom or other enclosure without direct access to the outdoors.

Collective housing

Indoor Premises - Residential - Dry: Entrance, living room, dining room, professional office with reception of customers

Indoor Premises - Housing - Dry: Bedrooms, personal office, storage room, changing room

Various

Cladding of bonded or mixed facades

Facade cladding with mechanical anchors

Kitchen worktops, bars, restaurants

Public bathroom countertops

System Certification





