

Model: TORTONA 1L PIAZZA

Codes: 100238603

Group: G-242


Format: 120X14,5X1,4CM



### ADDITIONAL NOTES

This material can show some pieces with whitening. Due to better usage of the wood, any order of this reference may contain mean percentage boards of between 10% and 15%.

### COMPOSITION



|         | Size        | Material           | Type of material       |
|---------|-------------|--------------------|------------------------|
| Layer 1 | 0.060-0.070 | Varnish            | Apresto Mate treatment |
| Layer 2 | 3           | Hardwood Layer     | Oak wood               |
| Layer 3 | 9           | Intermediate Layer | Wood or HDF slats      |
| Layer 4 | 2           | Backside           | Coniferous wood        |

### TOLERANCES




















|           |                 |  |
|-----------|-----------------|--|
| Curvature | 0.1% of length. |  |
|-----------|-----------------|--|

### LABORATORY TESTS

|                                |             |                               |
|--------------------------------|-------------|-------------------------------|
| Resistance to abrasion         | ≥500        | UNE-EN 13696:2009*            |
| Mass per surface               | 10.95 KG/M2 | EN 14342*                     |
| Thermal conductivity           | 0.18 W/M*K  | UNE-EN 12667:2002*            |
| Heat resistance                | 0.08 M2*K/W | UNE-EN 12667:2002*            |
| Formaldehyde emissions         | E1          | EN 717*                       |
| Moisture content               | 7.00%       | UNE-EN 13183-1/AC:2004*       |
| Flammability                   | Dfl-s1      | EN 13501*                     |
| Bulk density                   | 782 Kg/m3   | UNE-EN 323:1994*              |
| Biological durability          | Clase 1     | UNE EN 335 -1 ; UNE EN 335-2* |
| Slip resistance (pendulum-wet) | CL 1 (30)   | UNE 41901*                    |
| Slip resistance (pendulum-dry) | CL 3 (50)   | UNE 41902*                    |
| Slip resistance (dcof)         | 0.51        | ANSI A137.1*                  |



## FEATURES

-  Safety and joint durability are the main features of this easy installation system that guarantees the elimination of gaps between boards throughout the floor's lifetime. The pressure exerted between boards reinforces the union and prevents it from being carried out incorrectly.
-  Slight smoothing of the wood using a brush to achieve a surface with a slight relief.
-  L'ANTIC COLONIAL's varnishing, in two finishes, APRESTO (gloss) and APRESTO MATE (matte), provides a unique surface quality that satisfies the most demanding requirements. Advantages: It achieves the highest cleanliness because, since the pores are sealed, dirt and dust remain on the surface and can be easily cleaned.
-  Is suitable for installing on water radiant heating
-  Material with few knots on its surface that can have different sizes depending on the type of wood. These, along with any cracks that may appear, are covered with putty.
-  Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.
-  There are consistent color changes between pieces.
-  Material from a European country.
-  3 mm
-  Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.
-  Applying a color oil or varnish on the wood surface in order to get different color ranges.
-  Beveled cut on the long sides of the board in order to create a continuity effect
-  30 Quality product made with selected raw materials, guaranteeing its full residential use for 30 years as provided by L' Antic Colonial.
-  Format where only one board has been used to finish the entire base surface
-  It is necessary to apply adhesive for installing it.
-  OAK Made with oak wood.
-  Material from a North American country.
-  PanEuropean Forest Certification that guarantees to consumers the origin of the products from sustainably managed forests
-  It is necessary to apply adhesive for installing it.

## PACKING

|                              |                 |
|------------------------------|-----------------|
| Sales units per box          | 1.218 M2/BOX    |
| Sales units per pallet       | 34.104 M2/PAL   |
| Sales units per square meter | 1 M2            |
| Sale unit                    | M2              |
| Base unit                    | ST              |
| Net weight                   | 12.258621 KG/M2 |
| Gross weight                 | 12.902299 KG/M2 |

## SPECIAL PIECES

| SAP       | Description                           | Group | Boxes         | Pallet          | Units          | SKU | Basic Unit | Net Weight     | Gross weight   |
|-----------|---------------------------------------|-------|---------------|-----------------|----------------|-----|------------|----------------|----------------|
| 100153882 | IGUALACION TORTONA PIAZZA 4,5X270X1,3 | G-161 | 10 PIECES/BOX | 1000 PIECES/PAL | 8.23 PIECES/M2 | -   | -          | 1 KG/PIECES    | 1.02 KG/PIECES |
| 100176587 | MAMPERLAN TORTONA 1L PIAZZA 7X120X3   | G-163 | 2 PIECES/BOX  | 200 PIECES/PAL  | 11.9 PIECES/M2 | -   | -          | 1.58 KG/PIECES | 1.64 KG/PIECES |
| 100153889 | TRANSICION TORTONA PIAZZA 4X270X1,3   | G-161 | 10 PIECES/BOX | 1000 PIECES/PAL | 9.26 PIECES/M2 | -   | -          | 1 KG/PIECES    | 1.02 KG/PIECES |
| 100153896 | ZOCALO TORTONA PIAZZA 8X220X1,4       | G-128 | 12 PIECES/BOX | 600 PIECES/PAL  | 5.68 PIECES/M2 | -   | -          | 1.33 KG/PIECES | 1.38 KG/PIECES |

