

Model: AGED CLAY NATURE 120X250 (6)(A) Codes: 100181575 Absorption: Bla - Porcelanico (E<=0.1%)



Sistema DAPc[®] Declaración Ambiental de Productos de Construcción

DIMENSIONAL FEATURES UNE-EN ISO 10545-2					
Length	2500 MM				
Thickness	6 MM				
Width	1200 MM				
Length and width deviation	Below 0.15%		+/-0.3%*		
Side straightness deviation	Below 0.15%		+/-0.3%*		
Squareness deviation	Below 0.15%		+/-0.3%*		
Surface flatness deviation	Below 0.15%		+/-0.4%*		
*ISO-13006:2015 UNE-EN 14411:2017					

	MECHANICAL FEATURES UNE-EN ISO 10545-4-6-7-11
Breaking strenght	>1100 N
Modulus of rupture	>45 N/MM2
Abrasion resistance	<140
*ISO-13006:2015 UNE-EN 14411:2017	

	HYGIENIC FEATURES UNE-EN ISO 10545-13-14	
Chemical resistance	CLASE A	
Stain resistance	5	
*ISO-13006:2015 UNE-EN 14411:2017		

	ANTI-SLIP VALUE CEN/TS 41901/02, DIN-51130 y ASTM A137.
Dynamic coefficient of friction	>0.42
Slip resistance (pendulum-wet)	CL1
Slip resistance (ramp)	R9-A
Stain resistance	5
4s	DRY>36-LOW_WET>24-MOD.
Slip resistance (pendulum-dry)	>65
*ISO-13006:2015 UNE-EN 14411:2017	

SCOPE OF USE

Technical code-1 Technical code-2 Use on walls Dry interior floors

System Certification



100181575 AGED CLAY NATURE



PACKING				
Sales units per box	3 M2/BOX			
Sales units per pallet	66 M2/PAL			
Sales units per unit	3 M2/PIECE			



Do not use cleaning agents containing hydrofluoric acid. It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint. For big sizes, it is recomended to fix with mortars containing polymeric additives and to use the double glueing technique. Mosaic tiles must be grouted. This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by PORCELANOSA S.A.