

Model: CALACATTA GOLD SILK 120X250 (6)(A)

Codes: 100271959

Absorption: Bla - Porcelanico (E<=0.1%)





DIMENSIONAL FEATURES UNE-EN ISO 10545-2			
Length	2500 MM		
Thickness	6 MM		
Width	1200 MM		
Length and width deviation	Below 0.15%	+/-0.3%*	
Side straightness deviation	Below 0.15%	+/-0.3%*	
Squareness deviation	Below 0.15%	+/-0.3%*	
Surface flatness deviation	Below 0.15%	+/-0.4%*	

^{*}ISO-13006:2015 UNE-EN 14411:2017

MECHANICAL FEATURES UNE-EN ISO 10545-4-6-7-11		
Breaking strenght	>1100 N	
Modulus of rupture	>45 N/MM2	
Abrasion resistance	<140	

^{*}ISO-13006:2015 UNE-EN 14411:2017

HYGIENIC FEATURES UNE-EN ISO 10545-13-14		
Chemical resistance	CLASE A	
Stain resistance	5	
*ISO-13006:2015 UNE-EN 14411:2017		

	ANTI-SLIP VALUE CEN/TS 41901/02, DIN-51130 y ASTM A137.1
Slip resistance (pendulum-wet)	CLO
Stain resistance	5
4s	DRY>36-LOW_WET<25-HIGH
Slip resistance (pendulum-dry)	>45
*ISO-13006:2015 UNE-EN 14411:2017	

SCOPE OF USE		
Technical code-1	Use on walls	
Technical code-2	Dry interior floors	

System Certification









100271959 CALACATTA GOLD SILK



PACKING		
Sales units per box	3 M2/BOX	
Sales units per pallet	66 M2/PAL	
Sales units per unit	3 M2/PIECE	

System Certification





