

Model: TAJ MAHAL POLISHED 120X250(6)(A)

Codes: 100288131

Absorption: Bla - Porcelanico (E<=0.1%)





DIMENSIONAL FEATURES  UNE-EN ISO 10545-2				
Length	2500 MM			
Thickness	6 MM			
Width	1200 MM			
Length and width deviation	Below 0.15%	+/-0.3%*		
Side straightness deviation	Below 0.15%	+/-0.3%*		
Squareness deviation	Below 0.15%	+/-0.3%*		
Surface flatness deviation	Below 0.15%	+/-0.4%*		

<sup>\*</sup>ISO-13006:2015 UNE-EN 14411:2017

	MECHANICAL FEATURES UNE-EN ISO 10545-4-6-7-11
Breaking strenght	>1100 N
Modulus of rupture	>45 N/MM2
Abrasion resistance	<140

<sup>\*</sup>ISO-13006:2015 UNE-EN 14411:2017

HYGIENIC FEATURES  UNE-EN ISO 10545-13-14			
Chemical resistance	MIN B		
Stain resistance	5		
*ISO-13006:2015 UNE-EN 14411:2017			

	ANTI-SLIP VALUE CEN/TS 41901/02, DIN-51130 y ASTM A137.1
Slip resistance (pendulum-wet)	CLO
Stain resistance	5
4s	DRY>36-LOW_WET<25-HIGH
Slip resistance (pendulum-dry)	>45
*ISO-13006:2015 UNE-EN 14411:2017	

	SCOPE OF USE	
Technical code-1	Use on walls	
Technical code-2	Dry interior floors	

System Certification









100288131 TAJ MAHAL POLISHED



PACKING				
Sales units per box	3 M2/BOX			
Sales units per pallet	66 M2/PAL			
Sales units per unit	3 M2/PIECE			

System Certification





