

Model: TAJ MAHAL SILK 120X250(6)(A) Codes: 100288097 Absorption: Bla - Porcelanico (E<=0.1%)





DIMENSIONAL FEATURES UNE-EN ISO 10545-2			
Length	2500 MM		
Thickness	6 MM		
Width	1200 MM		
Length and width deviation	Below 0.15%		+/-0.3%*
Side straightness deviation	Below 0.15%		+/-0.3%*
Squareness deviation	Below 0.15%		+/-0.3%*
Surface flatness deviation	Below 0.15%		+/-0.4%*
*ISO-13006:2015 UNE-EN 14411:2017			

	MECHANICAL FEATURES UNE-EN ISO 10545-4-6-7-11
Breaking strenght	>1100 N
Modulus of rupture	>45 N/MM2
Abrasion resistance	<140
*ISO-13006:2015 UNE-EN 14411:2017	

	HYGIENIC F UNE-EN ISO 1	
Chemical resistance	CLASE A	
Stain resistance	5	
*ISO-13006:2015 UNE-EN 14411:2017		

	ANTI-SLIP VALUE CEN/TS 41901/02, DIN-51130 y ASTM A137.1
Slip resistance (pendulum-wet)	CLO
Stain resistance	5
4s	DRY>36-LOW_WET<25-HIGH
Slip resistance (pendulum-dry)	>45
*ISO-13006:2015 UNE-EN 14411:2017	

	SCOPE OF USE	
Use on walls		

Technical code-1 Technical code-2

Dry interior floors



100288097 TAJ MAHAL SILK



	PACKING	
Sales units per box	3 M2/BOX	
Sales units per pallet	66 M2/PAL	
Sales units per unit	3 M2/PIECE	



Do not use cleaning agents containing hydrofluoric acid. It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint. For big sizes, it is recomended to fix with mortars containing polymeric additives and to use the double glueing technique. Mosaic tiles must be grouted. This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by PORCELANOSA S.A.